

MATERIALS FOR INKJET

TECHNICAL DATA SHEET

PRODUCT CODE: MVPTRUCK1520/050



PRODUCT DESCRIPTION:

MJet Polytruck | Polymeric, 90 micron, White Gloss PVC film with a Grey Permanent Adhesive and **Air Escape** Liner.

APPLICATION:

Suitable for vehicle graphics, vehicle wrapping, truck wrapping.

PRINTING METHOD:

Suitable for Solvent, Eco-Solvent, Latex and UV curable inks.

TECHNICAL DATA:

SPECIFICATION	VALUE OR CONCLUSION	
Face Film	Type	Calendered polymeric soft PVC film
	Thickness	90 ± 10micron
	Color	White
	Gloss Degree	70 - 80°
	Shrinkage	≤1.5mm (3 years)
Adhesive	Type	Grey permanent glue
	Weight	40 ± 4g/m ²
	Application temperature	10~40°C
	180° Peeling Force (20mins)	≥16N/inch
	180° Peeling Force (24 hours)	≥18N/inch
Liner	Type	Double-sided PE-Coated silicon paper with Air Escape
	Weight	140 ± 10g/m ²
Shelf Condition & Shelf Life	12 months (Storage temperature 24°C, relative humidity 50 - 60%)	
Durability/Warranty	Up to 36 months	
Standard Width	1520mm	
Standard Length	50m	

Updated: Sept 2026

NATIONAL DISTRIBUTION - 086 1100 420

Email: nat.sales@maizey.co.za | Web: www.maizey.co.za | www.facebook.com/MaizeyPlastics/

maizey
FAMILY COMPANY. FAMILY VALUES est.1950